

MODEL U40-18X

EXPLOSION PROOF UPRIGHT FREEZER 0°C TO -40°C

Capacity [Cu. Ft.] 18 Cu. Ft.
Capacity [Liters] 505 Liters
Temperature Range [°C] 0°C to -40°C
Temperature Range [°F] 32°F to -40°F

Dimensions Width x Depth x Height
Exterior [Inches] 42" x 36" x 79.5"
Interior [Inches] 23" x 26" x 51.25"
Exterior [Centimeters] 106 x 91 x 201
Interior [Centimeters] 58 x 66 x 130

Refrigeration System Single Stage System
Compressors 1, Hermetic Compressor
Compressor Container Explosion Proof
Air Circulation Gravity Flow
Defrost Method Manual
Refrigerant HCFC & CFC Free
Exterior Powder Coated Steel
Interior Zinc Coated Galvanized Steel
Insulation Polyurethane (Ecomate) Foam
Inner Doors 5, Stainless Steel
Lockable Door Lockable with Padlock
Casters 4, Swivel with Locks
Storage 4 Adjustable Shelves, with
1 Base Shelf
Shipping Weight 900 Lbs.

Electrical

Standard Voltage 115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug 20A | 7.3A | NEMA 5-20
(Optional Voltages) 208 Volts, 230 Volts
Power Configuration Hardwired
Certification(s) UL Rated
Certification File Number SA10711
Certification Classification Class I, Division I & II,
Groups C & D

Controller

Display Type Explosion Proof, Digital

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor