

## ENERGY EFFICIENT MODEL VSC85-5

### CHEST ULTRA LOW FREEZER -40°C TO -85°C

<b>Capacity [ Cu. Ft. ]</b>	<b>5 Cu. Ft.</b>
<b>Capacity [ Liters ]</b>	<b>142 Liters</b>
<b>Temperature Range [ °C ]</b>	<b>-40°C to -85°C</b>
<b>Temperature Range [ °F ]</b>	<b>-40°F to -120°F</b>
Dimensions	Width x Depth x Height
Exterior [ Inches ]	40.5" x 31" x 43.75"
Interior [ Inches ]	30" x 18" x 16"
Exterior [ Centimeters ]	102 x 81 x 111
Interior [ Centimeters ]	76 x 46 x 40
Refrigeration System	Cascade-Style System
Compressors	2, Variable Speed
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	HCFC & CFC Free
Exterior	Powder Coated Steel
Interior	Zinc Coated Galvanized Steel
Insulation	Polyurethane (Ecomate) Foam
Additional Insulation	Beaded Foam Sub-Lids
Lockable Lid	Lockable with Padlock
Porthole	Optional 1/2"
Casters	4, Swivel with Locks
Storage	Optional Inventory Racks
Shipping Weight	525 Lbs.

#### Electrical

Standard Voltage	115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug ( Optional Voltages )	15A   13A   NEMA 5-15 208 Volts, 230 Volts
Certification(s)	ETL Listed

#### Controller

Display Type	Microprocessor, Digital
Touchscreen	Yes, 4.3" Color Display
Alarms	High/Low Temperature
Alarm Notification	Yes, Audible, Email, Text
Data Logging	Yes, Adjustable Intervals
Data Download	Yes, via USB, CSV Format
LAN Remote Access	Yes, via VNC
Min / Max Temperature	Yes, Display and Reset
Alarm Relay	Yes, Dry Contacts
Automatic Restart	Yes, After Power Failure

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



**Warranty** 1 Year Parts & Labor